

EasyHeat™ HB Cable

Pipe Freeze Protection, Constant Wattage, Hard-wired Cable. For Commercial Applications.

Product Overview

- The HB heating cable is complete with cold lead and ready for hard-wired installation on metal pipes to prevent freezing.

Applications

- Suitable for outdoor installation for refrigeration, condensation and air conditioning lines that are subject to freezing temperatures.

Features

- 120 Vac operating voltage.
- Keeps water flowing at ambient temperatures down to -40 °F (-40 °C).
- Includes ground braid, a black outer jacket, and a 2 ft (0.61 m) orange 14/3 cold lead with no thermostat or plug.
- Cables are rated at 7 Watts per foot (0.30 m).
- One year limited warranty.

Certifications

- UL Listed and CSA Certified to Canadian Safety Standards.

Notes

- Per NEC and CEC requirements ALWAYS use a ground fault protection device (GFEP) to reduce the danger of fire from a damaged or improperly installed heating cable. Electrical fault currents caused by damaged or improperly installed cable MAY NOT BE LARGE ENOUGH to trip a conventional circuit breaker.
- Heating cables must be installed in compliance with all national, state/provincial and local codes. Check with your local electrical inspector for specific details.
- Use on metal water pipes only. Do not use on plastic pipes.
- For outdoor use only. Do not use inside any type of building.
- The ambient temperature must be at least +15 °F (-10 °C) when attaching the cable to the pipe.
- This cable does not have an integral thermostat and must be controlled by a separately connected thermostat or by continuous monitoring of a qualified individual.

Product Selection

Catalog Number	Description	Amps	Carton Quantity	Carton Weight lb (kg)	UPC
HB01	3.28 ft (1 m) length, 23 Watts	0.19	20	10 (4.5)	06999600332
HB02	6.56 ft (2 m) length, 46 Watts	0.38	20	12 (5.4)	06999600333
HB03	9.84 ft (3 m) length, 69 Watts	0.58	20	15 (6.8)	06999600334
HB04	13.12 ft (4 m) length, 92 Watts	0.77	20	17 (7.7)	06999600335
HB05	16.41 ft (5 m) length, 115 Watts	0.96	20	20 (9.1)	06999600336
HB06	19.69 ft (6 m) length, 138 Watts	1.15	20	24 (10.9)	06999600337
HB07	22.97 ft (7 m) length, 161 Watts	1.34	10	13 (5.9)	06999600338
HB09	29.53 ft (9 m) length, 207 Watts	1.73	10	15 (6.8)	06999600339
HB12	39.37 ft (12 m) length, 275 Watts	2.29	10	17 (7.7)	06999600340
HB18	59.05 ft (18 m) length, 414 Watts	3.45	10	18 (8.2)	06999600341
HB24	78.74 ft (24 m) length, 551 Watts	4.59	10	21 (9.5)	06999600342

